



SCRAPER			
HP	RPM	TYP VOL @ LESS THAN 10,000 CPS	TYP VOL @ LESS THAN 100,000 CPS
2	21	300 GAL	60 GAL
3	15	750 GAL	150 GAL
5	12	2,500 GAL	500 GAL
7.5	11	5,000 GAL	1,000 GAL
10	11	7,500 GAL	1,500 GAL
15	12	10,000 GAL	2,000 GAL

TURBINE				
HP	RPM	(1) TURBINE	(2) TURBINES	(3) TURBINES
1.5	68	24"	20"	16"
		3055 GPM	2940 GPM	2042 GPM
2	63	28"	24"	20"
		4971 GPM	5248 GPM	3844 GPM
3	73	32"	28"	24"
		7480 GPM	8450 GPM	6792 GPM
5	68	36"	32"	28"
		11,322 GPM	13,838 GPM	11,901 GPM
7.5	73	40"	36"	32"
		14,832 GPM	18,727 GPM	17,424 GPM
10	73	44"	40"	36"
		20,880 GPM	25,214 GPM	24,235 GPM

NOTES:

1. 304 STN STL AND 316L STN STL OPTIONS
2. VARIOUS OPTIONS DEPENDING ON TANK SIZE AND APPLICATION
3. ALSO AVAILABLE IN F&D AND HEMISPHERIC BOTTOM HEAD
4. UHMW SCRAPER BLADE: MAX. WORKING TEMP. - 160° F.
 NYLON SCRAPER BLADE: MAX. WORKING TEMP. - 220° F.
 TEFLON SCRAPER BLADE: MAX. WORKING TEMP. - 400° F.

FELDMEIERS
EQUIPMENT

575 E.MILL STREET
 LITTLE FALLS, NY 13365

L:\PROJECTS\CUT SHEETS\AGITSCR TURB.DWG

REV - A EFFECTIVE 10/24/08

SCRAPER / TURBINE
 (THERMOMIXER) AGITATION
 STANDARD OPTIONS