



CAPACITY GAL/(LIT)	I.D. IN/(cm)	STR SD IN/(cm)	OAH IN/(cm)	# LEGS
500/(1,900)	48"/(122)	60"/(152)	105"/(267)	4
850/(3,200)	57"/(145)	72"/(183)	121"/(307)	4
1,000/(3,800)	66"/(168)	60"/(152)	114"/(290)	4
1,800/(6,800)	72"/(183)	96"/(244)	152"/(386)	4
2,500/(9,500)	84"/(213)	96"/(244)	158"/(401)	6
4,000/(15,100)	96"/(244)	120"/(305)	178"/(452)	6
5,300/(20,100)	110"/(279)	120"/(305)	182"/(462)	6
7,500/(28,400)	120"/(305)	144"/(366)	210"/(533)	6
9,800/(37,100)	120"/(305)	192"/(488)	258"/(655)	6

- NOTES:**
- 1) RATED CAPACITY IS TO THE TOP HEAD SEAM
  - 2) STANDARD LEG SUPPORT AND AGITATOR SUPPORT WELD FINISH IS SCOTCH-BRITE, 150 GRIT FINISH AVAILABLE AS AN OPTION.
  - 3) DUAL BALL SPRAY UNIT RATED FOR 80 GPM @ 25 PSIG
  - 4) SPRING LOADED SPLIT ROTARY CIP CONTAINMENT SEAL ASSEMBLY IS NOT DESIGNED TO RETAIN INTERNAL PRESSURE

**FELDMEIER  
EQUIPMENT**

575 E. Mill Street  
Little Falls, NY 13365

FILE#: L:\PROJECTS\CUTSHEETS\CVC.DWG

REV C EFFECTIVE 11/12/08

DIMENSION DRAWING  
'CVC' CONE BOTTOM  
SINGLE SHELL TANK