



CAPACITY GAL/(LIT)	I.D. IN/(cm)	STR SD IN/(cm)	OAH IN/(cm)	# LEGS
550/(2,100)	48\"/(122)	72\"/(183)	102\"/(259)	4
800/(3,000)	57\"/(145)	72\"/(183)	103\"/(262)	4
1,000/(3,800)	66\"/(168)	72\"/(183)	105\"/(267)	4
2,100/(8,000)	72\"/(183)	120\"/(305)	154\"/(391)	4
2,800/(10,600)	84\"/(213)	120\"/(305)	156\"/(396)	6
4,500/(17,000)	96\"/(244)	144\"/(394)	183\"/(465)	6
5,900/(22,300)	110\"/(279)	144\"/(394)	185\"/(470)	6

SS LEG SUPPORTS WITH ADJUSTABLE BALL FEET (NO EXPOSED THREADS) SEE TABLE FOR QTY INCLUDES: STN STL BASE PLATE WITH LEG GUSSETS, SKIP WELDED AND SILICONE CAULKED (OPTIONAL) FLANGED FOOT AVAILABLE

- NOTES:
- 1) RATED CAPACITY IS TO THE TOP HEAD SEAM
 - 2) STANDARD LEG SUPPORT AND AGITATOR SUPPORT WELD FINISH IS SCOTCH-BRITE, 150 GRIT FINISH AVAILABLE AS AN OPTION.
 - 3) DUAL BALL SPRAY UNIT RATED FOR 80 GPM @ 25 PSIG
 - 4) SPRING LOADED SPLIT ROTARY CIP CONTAINMENT SEAL ASSEMBLY IS NOT DESIGNED TO RETAIN INTERNAL PRESSURE

**FELDMEIER
EQUIPMENT**

575 E. Mill Street
Little Falls, NY 13365

FILE#: L:\PROJECTS\CUTSHEETS\CVF.DWG

REV C EFFECTIVE 11/12/08

DIMENSION DRAWING
'CVF' FLAT BOTTOM
SINGLE SHELL TANK