


CAPACITY GAL/(LIT)	I.D.	STR SD	OAH	O.D.	HTS SIDE	HTS BOTTOM	# ZONES	# LEGS	SHIP WT
200 GAL/(757)	48"	24"	67"	54-1/2"	17 SF	7.9 SF	1	4	#1,600
300 GAL/(1136)	54"	30"	75"	60-1/2"	20 SF	10.0 SF	1	4	#1,900
400 GAL/(1514)	57"	36"	82"	62-1/2"	26 SF	10.9 SF	1	4	#2,300
600 GAL/(2271)	60"	48"	95"	66-1/2"	35 SF	13.1 SF	1	4	#2,600
650 GAL/(2461)	66"	42"	91"	72-1/2"	44 SF	15.2 SF	1	4	#2,800
850 GAL/(3218)	72"	48"	97"	78-1/2"	51 SF	17.5 SF	1	4	#3,250
1,050 GAL/(3975)	72"	60"	109"	78-1/2"	64 SF	17.5 SF	2	4	#3,950
1,500 GAL/(5678)	78"	72"	123"	84-1/2"	85 SF	22.0 SF	2	6	#5,250
2,000 GAL/(7571)	84"	84"	137"	90-1/2"	111 SF	27.0 SF	2	6	#6,450
2,500 GAL/(9464)	90"	96"	150"	96-1/2"	131 SF	32.2 SF	2	6	#6,600
3,000 GAL/(11356)	96"	102"	158"	102-1/2"	169 SF	32.2 SF	2	6	#7,100
3,500 GAL/(13249)	96"	120"	176"	102-1/2"	202 SF	32.2 SF	2	6	#8,200
4,000 GAL/(15142)	102"	120"	177"	108-1/2"	210 SF	38.2 SF	3	6	#8800
5,000 GAL/(18927)	110"	130"	189"	116-1/2"	232 SF	45.0 SF	3	8	#9,300
6,000 GAL/(22713)	120"	130"	192"	126-1/2"	253 SF	49.0 SF	3	8	#10,200
8,000 GAL/(30283)	132"	144"	209"	138-1/2"	290 SF	72.0 SF	3	8	#11,300



NOTES:

- 1) BASIC HEADER HAS (2) PIPES PER ZONE, # ZONES DENOTES NUMBER OF SIDEWALL ZONES
- 2) PROCESSORS DESIGNED WITH 10% MIN FREEBOARD
- 3) DUAL BALL SPRAY UNIT RATED FOR 80 GPM @ 25 PSIG
- 4) SPRING LOADED SPLIT ROTARY CIP CONTAINMENT SEAL ASSEMBLY IS NOT DESIGNED TO RETAIN INTERNAL PRESSURE

FELDMEIER EQUIPMENT

575 E. Mill Street
Little Falls, NY 13365

FILE#: L:\PROJECTS\CUTSHEETS\EP-DDSHT.DWG

REV - EFFECTIVE 10/15/08

DIMENSION DRAWING
'EPD' DISH BOTTOM
DOME TOP PROCESSOR