



HORIZONTAL AGITATOR

*USDA ACCEPTED



Features

Designed for use in 3A Silos and Storage Tanks.

Designed for CIP without user adjustment.

Sanitary internal construction to ensure effective CIP.

Simplest design in the industry with (1) moving part.

Easy disassembly for periodic service.

Easy installation for field retrofits of existing vessels.

Standard design is suitable for milk, skim milk, cream, half & half, infant formula, etc...

Electropolished (3) bladed 22" diameter impeller is oversized to effectively agitate product at low speeds to minimize foaming.

Gearmotor Specs

Nord High Efficiency Helical Bevel Gearmotor.

2HP x 63 RPM Standard Configuration.

Stainless Steel hollowbore to prevent corrosion.

Foodgrade Lubricant.

Inverter Duty for operation from 0 to 90 RPM.

Compact Integral Motor design.

Options

All Stainless Steel Reducer & Motor.

USDA White Epoxy painted gearmotor.

Additional HP & RPM configurations available for high viscosity applications.

Available in a Non - 3A design with double mechanical seal or Teflon Packing seal.

Cleaning manifold to divert flow from other tank cleaning devices to the horizontal agitator.

**FELDMEIERS
EQUIPMENT, INC.**

Feldmeier Equipment, Inc.
Telephone: 315.454.8608
Fax: 315.454.3701
Email: ssstanks@feldmeier.com
Website: www.feldmeier.com

Manufacturing Facilities Syracuse, NY | Little Falls, NY | Montgomery, AL | Femley, NV | Shell Rock, IA