



NOTE:

1) FOR MIX & BLEND OPTION'S SEE (1) COMPARTMENT DRAWING

CAPACITY GALLON	'A'	'B'	'C'	'D'	'E'	'OAH'	LEGS	HTS BOTTOM PER COMP	EST WT LB
100	28"	34"	27-7/16"	39"	64"	44"	6	3.5 SQ. FT	1,180#
150	28"	34"	39-11/16"	39"	64"	56"	6	3.5 SQ. FT	1,310#
200	38"	44"	31-1/2"	49"	84"	48"	6	8.0 SQ. FT	1,455#
250	38"	44"	38"	49"	84"	54"	6	8.0 SQ. FT	1,600#
300	38"	44"	44-15/16"	49"	84"	61"	6	8.0 SQ. FT	1,990#
400	50"	56"	36-7/8"	62"	109"	53"	6	14.5 SQ. FT	2,890#
500	50"	56"	45-1/8"	62"	109"	61"	6	14.5 SQ. FT	3,325#
600	50"	56"	53-3/8"	62"	109"	70"	6	14.5 SQ. FT	3,750#
800	66"	60"	50-15/16"	67"	142"	67"	6	21.5 SQ. FT	5,150#
1,000	66"	60"	62-5/8"	67"	142"	81"	6	21.5 SQ. FT	5,825#

NOTES:

- 1) BASIC HEADER DESIGN, (1) INLET, (2) OUTLETS 1-1/4" NPT MALE HTS CONNECTIONS
- 2) HEAT TRANSFER SURFACE RATED FOR 100 PSIG AT 350 DEG. F STANDARD
- 3) ASME 'U' CERTIFICATION AVAILABLE
- 4) SINGLE SPRAY UNIT RATED FOR 40 GPM @ 25 PSIG

**FELDMEIER
EQUIPMENT**

575 E.MILL STREET
LITTLE FALLS, NY 13365

L:\PROJECTS\CUT SHEETS\MB2COMP.DWG

REV - EFFECTIVE 9/2004

DIMENSION DRAWING
MIX & BLEND (2) COMPARTMENT
INSULATED TANK