



CAPACITY GALLON	'A'	'B'	'C'	'D'	'E'	'OAH'	LEGS	HTS BOTTOM	EST WT LB
100	28"	34"	27-7/16"	39"	33"	44"	4	3.5 SQ. FT	740#
150	28"	34"	39-11/16"	39"	33"	56"	4	3.5 SQ. FT	800#
200	38"	44"	31-1/2"	49"	43"	48"	4	8.0 SQ. FT	860#
250	38"	44"	38"	49"	43"	54"	4	8.0 SQ. FT	955#
300	38"	44"	44-15/16"	49"	43"	61"	4	8.0 SQ. FT	1,300#
400	50"	56"	36-7/8"	62"	56"	53"	4	14.5 SQ. FT	1,770#
500	50"	56"	45-1/8"	62"	56"	61"	4	14.5 SQ. FT	2,050#
600	50"	56"	53-3/8"	62"	56"	70"	4	14.5 SQ. FT	2,325#
800	66"	60"	50-15/16"	67"	73"	67"	4	21.5 SQ. FT	3,110#
1,000	66"	60"	62-5/8"	67"	73"	79"	4	21.5 SQ. FT	3,540#

- NOTES:**
- 1) BASIC HEADER DESIGN, (1) INLET, (2) OUTLETS 1-1/4" NPT MALE HTS CONNECTIONS
  - 2) HEAT TRANSFER SURFACE RATED FOR 100 PSIG AT 350 DEG. F STANDARD
  - 3) ASME 'U' CERTIFICATION AVAILABLE
  - 4) SINGLE SPRAY UNIT RATED FOR 40 GPM @ 25 PSIG

**FELDMEIER  
EQUIPMENT**

575 E.MILL STREET  
LITTLE FALLS, NY 13365

L:\PROJECTS\CUT SHEETS\MB1COMP.DWG

REV - EFFECTIVE 9/2004

DIMENSION DRAWING  
MIX & BLEND (1) COMPARTMENT  
INSULATED TANK