



# HORIZONTAL AGITATOR

\*USDA ACCEPTED



## Features

- Designed for use in 3A Silos and Storage Tanks.
- Designed for CIP without user adjustment.
- Sanitary internal construction to ensure effective CIP.
- Simplest design in the industry with (1) moving part.
- Easy disassembly for periodic service.
- Easy installation for field retrofits of existing vessels.
- Standard design is suitable for milk, skim milk, cream, half & half, infant formula, etc...
- Electropolished (3) bladed 22" diameter impeller is oversized to effectively agitate product at low speeds to minimize foaming.

## Gearmotor Specs

- Nord High Efficiency Helical Bevel Gearmotor.
- 2HP x 63 RPM Standard Configuration.
- Stainless Steel hollowbore to prevent corrosion.
- Foodgrade Lubricant.
- Inverter Duty for operation from 0 to 90 RPM.
- Compact Integral Motor design.

## Options

- All Stainless Steel Reducer & Motor.
- USDA White Epoxy painted gearmotor.
- Additional HP & RPM configurations available for high viscosity applications.
- Available in a Non - 3A design with double mechanical seal or Teflon Packing seal.
- Cleaning manifold to divert flow from other tank cleaning devices to the horizontal agitator.

**FELDMEIERS  
EQUIPMENT, INC.**

Feldmeier Equipment, Inc.  
Telephone: 315.454.8608  
Fax: 315.454.3701  
Email: [ssstanks@feldmeier.com](mailto:ssstanks@feldmeier.com)  
Website: [www.feldmeier.com](http://www.feldmeier.com)

Manufacturing Facilities Syracuse, NY | Little Falls, NY | Montgomery, AL | Femley, NV | Shell Rock, IA